

## PIC14000 Calibration Parameters

*Author: Richard Fisher  
Standard Microcontroller and  
ASSP Division*

**Caution:**

When using a WINDOWED DEVICE, the calibration data will be lost if the device is erased. Care should be exercised to insure that factory calibration data is not lost. Microchip does not recommend using code protection in a windowed device.

Due to the photosensitivity of semiconductors, the analog peripherals may not function properly if the window protection label is not in place during device operation.

### INTRODUCTION

This application note discusses the PIC14000 calibration constants and calibration procedures.

The PIC14000 has several analog peripherals. Like all CMOS circuitry the parametric values vary with process, temperature, voltage, and time.

The PIC14000 has been designed to minimize the effect of these variations. In addition, each device is calibrated at factory test by measuring several key parameters and storing these values into EPROM at specified locations. The customer's application program may access this data and use it to mathematically compensate for device variations.

Collectively, these data values are referred to as calibration constants. They are listed in Table 4-1 in the PIC14000 Data Sheet (DS40122A).

### CALIBRATION DATA

The PIC14000 calibration constants are shown in Table 1.

**TABLE 1: CALIBRATION CONSTANTS**

Parameter	Symbol
A/D Slope reference ratio	KREF
Bandgap reference voltage	KBG
Temperature sensor voltage	VTHERM
Temperature sensor voltage slope	KTC
Internal oscillator frequency multiplier	FOSC
Watch Dog Timer (WDT) time-out	TWDT

Table 2 show an example of PIC14000 calibration constants and their locations.

The first four parameters in the table are in 32-bit floating point representation. Each parameter has an exponent byte, and three bytes of mantissa. (For information on floating point algorithms, refer to AN575.) The last two parameters are single-byte numbers.

**TABLE 2: TYPICAL CALIBRATION CONSTANTS**

Constant	Address	Value	Byte 1	Byte 2	Byte 3	Byte 4
KREF	0FC0:0FC3	0.1259	7C	00	F8	DD
KBG	0FC4:0FC7	1.1842	7F	17	93	02
VTHERM	0FC8:0FCB	1.0766	7F	09	CC	CD
KTC	0FCC:0FCF	0.0037	76	75	B3	3C
FOSC	0FD0	4.65	A5	—	—	—
TWDT	0FD2	16	10	—	—	—

Note: For the 4-byte constants, Byte 1 is the exponent, while Byte 2, 3, and 4 specify Mantissa High Byte, Middle Byte, and Low Byte, respectively. For the 1-Byte constants, the value occupies only Byte 1.

PRO MATE is a trademark of Microchip Technology Inc.

## USING CALIBRATION DATA

The calibration constants should be used by the application firmware to obtain the best accuracy.

KREF and KBG are used in A/D conversions. For further details, see AN624.

VTHERM and KTC are used for the internal temperature sensor. To use these parameters to calculate temperature, see AN624.

FOSC is a 1-byte value that represents the measured internal oscillator frequency. The internal oscillator frequency can be calculated as follows:

$$f = \left( 3 + \frac{F_{OSC}}{100} \right) \text{MHz}$$

FOSC can be used to compensate device internal clock variations for time critical applications such as USART baud rate generation.

TWDT is a 1-byte value that is the watchdog time-out in milliseconds without using the postscaler counter. The postscaler counter can extend the WDT time out up to 2.5 seconds. See the PIC14000 Data Sheet, Section 6, for further details

## PARAMETER VARIATION

Table 3 lists the "Maximum Parameter Variation" attainable when the calibration data is not used. This data is based on measurement over the temperature range of -40°C to +85°C and over the operating VDD range of 2.7V to 6.0V, unless otherwise specified. For further details, refer to the PIC14000 Data Sheet.

**TABLE 3: MAXIMUM PARAMETER VARIATION WITHOUT CALIBRATION (PRELIMINARY)**

Symbol	Parameter	Maximum Variation
KREF	A/D slope reference ratio	+/- 2.2%
KBG	Bandgap reference voltage	+/- 4.2%
VTHERM	Temperature sensor voltage	+/- 12.4% (Note 1)
KTC	Temperature sensor coefficient	+/- 5%
TEMPINT	Calculated temperature	+/- 35°C
TWDT	WDT Timeout Period	+/- 60% (Note 2)

Note 1: At 25°C, +/- 2°C, over VDD range.

2: 7 msec to 33 msec over temperature, VDD = 5.0V

If these accuracies are adequate for the task at hand, no further calibrations are necessary. If greater accuracy is needed, the calibration constants must be used.

Table 4 lists the "Expected Parameter Variation with Calibration." This data is based on measurements using the calibration data (measured at 25°C) over the temperature range of 0°C to +50°C and at the operating VDD = 5.0V unless otherwise specified. For further details, refer to the PIC14000 Data Sheet.

**TABLE 4: EXPECTED VARIATION OF PARAMETERS WITH CALIBRATION (PRELIMINARY)**

Symbol	Parameter	Maximum Variation
KREF	A/D slope reference ratio	+/- 0.13%
KBG	Bandgap reference voltage	+/- 0.058%
VTHERM	Temperature sensor voltage	+/- 0.71% (Note 1)
KTC	Temperature sensor coefficient	Calculated as the slope between 25°C and TMAX (NOTE 2)
TEMPINT	Calculated temperature	+/- 2°C (Note 3)
TWDT	WDT Timeout Period	+/- 13.8%

Note 1: At 25° C, +/- 2°C.

2: Tmax = 70°C for commercial temperature, 85°C for industrial temperature.

3: Refer to AN624 for description of TEMPINT.

---

## PROGRAMMING THE PIC14000

### Non-Windowed Parts

Non-windowed parts are programmed just like any PIC16CXX processor. The calibration area is write-protected during factory calibration and will not be overwritten by PRO MATE.

### Windowed Parts

**Caution:**

Windowed parts must not be write-protected. If the parts are erased by ultraviolet light, the calibration parameters are lost and can not be reprogrammed once the part has been write-protected.

Calibration data must be read out and saved before erasing a windowed part. There is no way to recreate these values, so if they are lost the part can no longer be calibrated.

The calibration data is read by the PRO MATE just like the rest of the code space. After reading, it must be saved as a Hex file. The entire memory space will be saved from 0 to 0xFFFF. There is no way to save a part of the memory space.

To erase a windowed part:

1. Read part into the PRO MATE buffer.
2. If 000h - 0FBFh is not blank, use the Fill Prog Buffer command to set all bits to '1'.
3. Save the buffer content as a Hex file.

**Note:**

The calibration data, and hence this file, will be different for each PIC14000. Don't forget to label the file and the part!

4. Use ultraviolet light to erase the part.
5. Load the saved Hex file (in step 3) into the PRO MATE buffer.
6. Program the part.

The part is now at the same state as it was when the factory shipped it. Load your code and program in the usual fashion.

If desired, after the calibration data file has been loaded to PRO MATE, the application program may be loaded and the whole part programmed at once.

### Checksum

The checksum bytes listed in the data sheet are only for use by the PIC14000 programmer. There is no way for an application program to utilize this checksum data. Note that there are special bytes added to this space so that the checksum of the entire calibration space totals zero. This means that the calibration factors, which vary from part to part, will not affect the user's code checksum, which may be used for program verification.

## PROGRAM EXAMPLES

At the end of this application note are two code samples that may be used to access the calibration data. The first reads the entire table and stores the values in RAM. The second program can be used to restore calibration parameters, if accidentally erased.

## SUMMARY

This application note has discussed the calibration constants programmed at Microchip Technology Inc. into the PIC14000. It has discussed the effect of these calibration constants on system accuracy. It has also covered the erasing and reprogramming procedures.

# AN621

## PIC14000 CALIBRATION CONSTANTS

```
list    p=14000, n=74, st=off
errorlevel -306;suppress reporting of message "Crossing page boundary -- ensure page bits are
set"
        ;from list file

include pl4000.inc

__CONFIG _CPC_ON & _CPU_OFF & _CPP_OFF & _PWRTE_ON & _WDT_OFF & _FOSC_RC

; __CONFIG is a MPASM directive used to embed the Configuration Word setup into.HEX file
; See PIC14000 Data Book for additional information on the Configuration Word

;*****
;* The code listed below can be implemented to read the 64 bytes of data located in the PIC14000
;* Calibration Space (0FC0h - 0FFh). The data bytes read will be saved to 64 consecutive RAM
;* locations starting at location "CAL_ARRAY".
;*
;*****

; REGISTER EQUATES

        ORG 0x20
TABLE_OFFSET    RES .1           ;reserve 1 byte for table offset
KREF_PNTR       RES .4           ;reserve 4 bytes for cal data
KBG_PNTR        RES .4           ;reserve 4 bytes for cal data
VTHRM_PNTR      RES .4           ;reserve 4 bytes for cal data
KTC_PNTR        RES .4           ;reserve 4 bytes for cal data
KIN_PNTR        RES .40          ;reserve 40 bytes for cal data
CAL_DATA_CHKSUM_PNTR RES.8 ;reserve 8 bytes for cal data

CAL_ARRAY SET    KREF_PNTR

;***** COPIES CALIBRATION DATA TO RAM
        ORG 0x00
        clrf INTCON              ;ensure INTCON is cleared
        clrf PCLATH              ;ensure PCLATH is cleared
        clrf STATUS              ;
        goto start               ;

        ORG 0x04
isr     goto    isr              ;do nothing

start   movlw   high read_cal_table;move high byte of read_cal-table
        movwf  PCLATH            ;address into PCLATH
        call   read_cal_table    ;
        clrf  PCLATH            ;reset PCLATH
stop    goto    stop            ;wait here

        ORG 0xF00
read_cal_table clrfTABLE_OFFSET    ;initialize table offset register
        movlw  CAL_ARRAY          ;call routine for moving cal space data
        ;into RAM
        movwf  FSR                ;initialize RAM array pointer

next_constantmovfTABLE_OFFSET,w    ;move array offset value into W Reg.
        call   cal_table          ;get a byte of CAL data
        movwf  INDF              ;save constant to RAM
        incf  FSR,f              ;increment RAM cal-array pointer
        incf  TABLE_OFFSET,f    ;point to next calibration data word
        movlw 0x3B              ;
```

```
    subwf  TABLE_OFFSET,w      ;test if all valid cal data has been read
    btfss  STATUS,Z            ;test if result of subtract (compare) is zero
    goto   next_constant       ;go read another table element
    return

    ORG    0xFBF

cal_table  addwf  PCL,f         ;Add table offset to PC

    END
```

## CALIBRATION DATA TABLE

```
list    p=14000,n=74,st=off
errorlevel -306;suppress reporting of message "Crossing page boundary -- ensure page bits are
set"
        ;from list file

include pl4000.inc

__CONFIG _CPC_ON & _CPU_OFF & _CPP_OFF & _PWRTE_ON & _WDT_OFF & _FOSC_RC

; __CONFIG is a MPASM directive used to embedd the Configuration Word setup into.HEX file
; See PIC14000 Data Book for additional information on the Configuration Word

;*****
;* TITLE:   Calibration data table
;* PURPOSE: Create a hex file of the calibration data to program into the PIC14000
;* DESCRIPTION:
;* This table is only needed if you erase, accidentally or otherwise, the existing
;* calibration data that was preprogrammed in the PIC14000.
;* In order to get the calibration data, you have to read the PIC14000 (before
;* you erase it) and save the data in a hex or text file. So, it is a good idea
;* to read the cal data and save it before you start your development work.
;*
;*****

        ORG 0xFC0                ;Start of calibration data

;
;-----Microchip modified IEEE754
; |      | mantissa | mantissa | mantissa | 32-bit floating point format
; | exp  | hi byte  | mid byte | low byte | (see appnote AN575)
;-----
Kref    DT    0x7B,    0x64,    0xC3,    0xEE;A/D Slope Ref.
Kbg     DT    0x7F,    0x13,    0x35,    0x40;Bandgap Ref. Voltage
Vthrm   DT    0x7F,    0x07,    0xC8,    0xB5;Temperature Sensor Voltage
Ktc     DT    0x76,    0x75,    0xB3,    0x3C;Volts / (degree Celsius)
Kin     DT    0x69                ;Fosc (unsigned byte)

fill_startFILL(retlw 0xFF), (CAL_DATA_CHKSUM - fill_start);FD1 - FF8 = retlw 0xFF

        org 0xFF9                ;cal data checksum address

CAL_DATA_CHKSUM                ;calibration data checksum FC0H-FF8H
        DT    0xC3,0xB5
        FILL0x3FFF,3            ;next three words are not unused
        org 0xFFE

        DW    0x12D6                ;special checksum data
        ;makes calibration space (FC0H-FCDH)
        ;checksum equal 0000H. Hence,
        ;the cal data has no effect on the
        ;device checksum calculation

        DW    0x0000                ;Checksum of cal space = 0000H
        end
```

**NOTES:**

---

---

# WORLDWIDE SALES & SERVICE

---

---

## AMERICAS

### Corporate Office

Microchip Technology Inc.  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 602 786-7200 Fax: 602 786-7277  
Technical Support: 602 786-7627  
Web: <http://www.microchip.com/>

### Atlanta

Microchip Technology Inc.  
500 Sugar Mill Road, Suite 200B  
Atlanta, GA 30350  
Tel: 770 640-0034 Fax: 770 640-0307

### Boston

Microchip Technology Inc.  
5 Mount Royal Avenue  
Marlborough, MA 01752  
Tel: 508 480-9990 Fax: 508 480-8575

### Chicago

Microchip Technology Inc.  
333 Pierce Road, Suite 180  
Itasca, IL 60143  
Tel: 708 285-0071 Fax: 708 285-0075

### Dallas

Microchip Technology Inc.  
14651 Dallas Parkway, Suite 816  
Dallas, TX 75240-8809  
Tel: 214 991-7177 Fax: 214 991-8588

### Dayton

Microchip Technology Inc.  
Suite 150  
Two Prestige Place  
Miamisburg, OH 45342  
Tel: 513 291-1654 Fax: 513 291-9175

### Los Angeles

Microchip Technology Inc.  
18201 Von Karman, Suite 1090  
Irvine, CA 92715  
Tel: 714 263-1888 Fax: 714 263-1338

## AMERICAS (continued)

### New York

Microchip Technology Inc.  
150 Motor Parkway, Suite 416  
Hauppauge, NY 11788  
Tel: 516 273-5305 Fax: 516 273-5335

### San Jose

Microchip Technology Inc.  
2107 North First Street, Suite 590  
San Jose, CA 95131  
Tel: 408 436-7950 Fax: 408 436-7955

### Toronto

Microchip Technology Inc.  
5925 Airport Road, Suite 200  
Mississauga, Ontario L4V 1W1, Canada  
Tel: 905 405-6279 Fax: 905 405-6253

## ASIA/PACIFIC

### Hong Kong

Microchip Technology  
Rm 3801B, Tower Two  
Metroplaza,  
223 Hing Fong Road,  
Kwai Fong, N.T., Hong Kong  
Tel: 852 2 401 1200 Fax: 852 2 401 3431

### Korea

Microchip Technology  
168-1, Youngbo Bldg. 3 Floor  
Samsung-Dong, Kangnam-Ku,  
Seoul, Korea  
Tel: 82 2 554 7200 Fax: 82 2 558 5934

### Singapore

Microchip Technology  
200 Middle Road  
#10-03 Prime Centre  
Singapore 188980  
Tel: 65 334 8870 Fax: 65 334 8850

### Taiwan

Microchip Technology  
10F-1C 207  
Tung Hua North Road  
Taipei, Taiwan, ROC  
Tel: 886 2 717 7175 Fax: 886 2 545 0139

## EUROPE

### United Kingdom

Arizona Microchip Technology Ltd.  
Unit 6, The Courtyard  
Meadow Bank, Furlong Road  
Bourne End, Buckinghamshire SL8 5AJ  
Tel: 44 1 628 850303 Fax: 44 1 628 850178

### France

Arizona Microchip Technology SARL  
Zone Industrielle de la Bonde  
2 Rue du Buisson aux Fraises  
91300 Massy - France  
Tel: 33 1 69 53 63 20 Fax: 33 1 69 30 90 79

### Germany

Arizona Microchip Technology GmbH  
Gustav-Heinemann-Ring 125  
D-81739 Muenchen, Germany  
Tel: 49 89 627 144 0 Fax: 49 89 627 144 44

### Italy

Arizona Microchip Technology SRL  
Centro Direzionale Colleoni  
Palazzo Taurus 1 V. Le Colleoni 1  
20041, Agrate Brianza, Milan Italy  
Tel: 39 39 689 9939 Fax: 39 39 689 9883

## JAPAN

Microchip Technology Intl. Inc.  
Benex S-1 6F  
3-18-20, Shin Yokohama  
Kohoku-Ku, Yokohama  
Kanagawa 222 Japan  
Tel: 81 45 471 6166 Fax: 81 45 471 6122

5/10/96



**MICROCHIP**

All rights reserved. © 1996, Microchip Technology Incorporated, USA. 5/96

Information contained in this publication regarding device applications and the like is intended through suggestion only and may be superseded by updates. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchip's products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, under any intellectual property rights. The Microchip logo and name are registered trademarks of Microchip Technology Inc. All rights reserved. All other trademarks mentioned herein are the property of their respective companies.