

MGFC39V3742A

PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

3.7~4.2GHz BAND 8W INTERNALLY MATCHED GaAs FET

DESCRIPTION

The MGFC39V3742A is an internally impedance-matched GaAs power FET especially designed for use in 3.7 ~ 4.2 GHz band amplifiers. The hermetically sealed metal-ceramic package guarantees high reliability.

FEATURES

- Class A operation
- Internally matched to 50Ω system
- High output power
 $P_{1dB} = 8W$ (TYP) @ 3.7 ~ 4.2 GHz
- High power gain
 $G_{LP} = 10$ dB (TYP) @ 3.7 ~ 4.2 GHz
- High power added efficiency
 $\eta_{add} = 31\%$ (TYP) @ 3.7 ~ 4.2 GHz, P_{1dB}
- Hermetically sealed metal-ceramic package
- Low distortion [Item: -51]
 $IM_3 = -45$ dBc (TYP) @ $P_o = 28$ (dBm) S.C.L.

APPLICATION

- Item-01: 3.7 ~ 4.2 GHz band power amplifier
- Item-51: Digital radio communication

QUALITY GRADE

- IG

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

Symbol	Parameter	Ratings	Unit
V _{GD0}	Gate to drain voltage	-15	V
V _{GSO}	Gate to source voltage	-15	V
I _D	Drain current	7.5	A
I _{GR}	Reverse gate current	-20	mA
I _{GF}	Forward gate current	42	mA
P _T	Total power dissipation *1	42.8	W
T _{ch}	Channel temperature	175	°C
T _{stg}	Storage temperature	-65 ~ +175	°C

*1: T_c = 25°C


ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Symbol	Parameter	Test conditions	Limits			Unit
			Min	Typ	Max	
I _{DSS}	Saturated drain current	V _{DS} = 3V, V _{GS} = 0V	—	—	7.5	A
g _m	Transconductance	V _{DS} = 3V, I _D = 2.2A	—	2	—	S
V _{GS(off)}	Gate to source cut-off voltage	V _{DS} = 3V, I _D = 20mA	—	—	-4.5	V
P _{1dB}	Output power at 1dB gain compression	V _{DS} = 10V, I _D = 2.4A, f = 3.7~4.2GHz	38	39	—	dBm
G _{LP}	Linear power gain		9	10	—	dB
I _D	Drain current		—	—	3.0	A
η _{add}	Power added efficiency		—	31	—	%
* IM ₃	3rd order IM distortion *1		-42	-45	—	dBc
R _{th(ch-c)}	Thermal resistance *2		ΔV _f method	—	—	3.5

*1: Item-51, 2-tone test P_o = 28 dBm Single Carrier Level f = 4.2 GHz Δf = 10 MHz *2: Channel to case

OUTLINE DRAWING

Unit: millimeters (inches)



RECOMMENDED BIAS CONDITIONS

- V_{DS} = 10V
- I_D = 2.4A
- R_g = 50Ω
- Refer to Bias Procedure


PRELIMINARY

Notice: This is not a final specification.
Some parametric limits are subject to change.


3.7~4.2GHz BAND 8W INTERNALLY MATCHED GaAs FET

TYPICAL CHARACTERISTICS


P_{1dB} , G_{LP} vs. f



P_o , η_{add} vs. P_{in}



P_o , IM_3 vs. P_{in}



S PARAMETERS ($T_a=25^\circ C$, $V_{DS}=10V$, $I_{DS}=2.4A$)

f (GHz)	S Parameters (TYP.)							
	S_{11}		S_{21}		S_{12}		S_{22}	
	Magn.	Angle (deg.)	Magn.	Angle (deg.)	Magn.	Angle (deg.)	Magn.	Angle (deg.)
3.7	0.47	-180	4.295	26	0.069	-37	0.29	-124
3.8	0.48	162	4.426	3	0.072	-59	0.33	-154
3.9	0.44	136	4.472	-22	0.079	-82	0.37	-176
4.0	0.25	91	4.380	-48	0.084	-108	0.42	165
4.1	0.13	-55	4.181	-75	0.083	-136	0.46	141
4.2	0.34	-114	3.990	-103	0.078	-164	0.46	114